

# MATERIAL SAFETY DATA SHEET

# 1. COMPANY AND PRODUCT IDENTIFICATION

**DUNCAN ENTERPRISES EMERGENCY TELEPHONE NUMBERS** 

5673 East Shields Avenue Health Emergency: 559-291-4444 7:00 am - 3:30 pm Fresno, CA 93727

Pacific Standard Time

559-291-4444 Spill and Off-Hour

559-291-9444 (Fax) Health Emergencies: 800-424-9300 U.S. and Canada

703-527-3887 Outside U.S. and

Canada (Collect)

**DUNCAN E-Z STROKE® TRANSLUCENT UNDERGLAZES Product Name:** 

**Product Type:** Nontoxic Ceramic Glaze

# 2. COMPOSITION / INFORMATION ON INGREDIENTS

The ingredients in this formulation are a trade secret. All ingredients in the formula are non-hazardous. unless specified in Sections 3 and 15.

# 3. HAZARDS IDENTIFICATION

**HMIS Hazard Ratings for Product** 

Health: 0 = MinimalFlammability: 0 1 = SlightReactivity: 0 2 = Moderate Personal Protection: See Section 8 3 = Serious

> 4 = Severe \* = Chronic Effects

# **4. FIRST AID MEASURES**

Flush eyes with large amounts of water until irritation subsides. Consult a physician Eye Contact:

if irritation persists.

Skin Contact: Wash affected skin areas thoroughly with soap and water. Consult a physician if

irritation persists.

Inhalation: Move subject to fresh air.

If swallowed, give two glasses of water to drink. Consult a physician. Never give Ingestion:

anything by mouth to an unconscious person.

# **5. FIRE FIGHTING MEASURES**

**Autoignition Temperature:** Nonflammable **Flash Point:** Not Applicable **Upper Explosive Limit (%):** Not Applicable Lower Explosive Limit (%): Not Applicable

**Extinguisher Media:** Product is nonflammable – Use extinguishing

media appropriate for surrounding fire

Not Applicable **Special Firefighting Procedures:** Fire & Explosion Hazards: Not Applicable **NFPA Flammability Hazard Class:** 0 = Insignificant

#### **6. ACCIDENTAL RELEASE MEASURES**

**Spill or Leak Procedures:** Spills should be taken up with suitable absorbent material and placed in

containers. Spill areas can be washed with water; collect wash water for

approved disposal. Do not flush to storm sewer or waterway.

For safety and environmental precautions, please review entire Material Safety Data Sheet for necessary information.

# 7. HANDLING AND STORAGE

**Storage Temperature:** 40° - 100°F

Handling / Storage: Protect from freezing; keep container sealed when not in use

Ventilation Requirements: General

# **8. EXPOSURE CONTROL AND PERSONAL PROTECTION**

Conditions Under Which Personal Protective Equipment Required

**Eye Protection Requirements:** Wear safety glasses with side shields

Glove Requirements: Gloves are not normally required for foreseeable

conditions of use

**Clothing Requirements:** Protective clothing is normally not necessary for

foreseeable conditions of use

Change / Removal of Clothing: None required

Wash Requirements: Good hygiene practices should be followed

Respirator Requirements: NIOSH approved respirator for sprays and mists recommended

if using a sprayer

**Ventilation Requirements:** General; local exhaust ventilation recommended when spraying

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Physical Description: Colored liquid. Odorless

 pH:
 7 - 10

 Boiling Point:
 212°F

 Freezing Point:
 32°F

 Melting Point:
 1800°F

 Solubility in Water:
 Miscible

 Specific Gravity (Water = 1):
 1.3 - 1.8

**Bulk Density:** 10.8 – 15.0 lb / gal

Evaporation Rate (Water = 1):

Vapor Pressure: 17.5 mm Hg @ 20°C (68°F)

Autoignition Temperature:Not ApplicableFlash Point:Not ApplicableOxidizing Properties:Not Applicable

# 10. STABILITY AND REACTIVITY

Stability:StableIncompatible Materials:None knownNFPA Reactivity Hazard Class:0 = Insignificant

Hazardous Decomposition Products: Avoid fumes when firing

Hazardous Polymerization: Will not occur
Conditions to Avoid: None Known
Page 2 of 4

Duncan Enterprises Material Safety Data Sheet - E-Z Stroke Translucent Underglazes

#### 11. TOXICOLOGICAL INFORMATION

Short - Term Effects of Exposure

Routes of Entry: Inhalation: No Skin Contact: No Ingestion: Yes

Acute Effects – Eye: Abrasive, can scratch eyes

Acute Effects – Skin Contact: No hazard in normal industrial use.

Acute Effects – Inhalation: No hazard in normal industrial use.

Acute Effects – Ingestion: No hazard in normal industrial use.

**Long – Term Effects of Exposure** 

Effect of Chronic Exposure: This product should be considered non – hazardous and has no known

chronic effects.

Target Organs: Not applicable

Carcinogenicity: IARC Monographs: No NTP: No OSHA Regulated: No

# 12. ECOLOGICAL INFORMATION

No Applicable Data

# 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Waste disposal should be in accordance with existing Federal, State,

and Local environmental regulations.

# **14. TRANSPORT INFORMATION**

U.S. Department of Transportation Information

**DOT Shipping Name:** Glazes or Stains, Ceramic or Pottery, Artists or Hobbyists Liquid

DOT Hazard Class: 88690 Sub. 1

**DOT Reportable Quantity:** None

# 15. REGULATORY INFORMATION

**TSCA**: All components are on the TSCA Inventory

**FDA:** 21CFR175.105

**SARA/Title III:** This product contains no substances at or above the reported threshold under

Section 313, based on available data.



Products bearing the Nontoxic Product Seal are certified in a program of toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200(c).

# **16. OTHER INFORMATION**

# **Table of Abbreviations**

**ACGIH** American Conference of Governmental Industrial Hygienists

ANSI American National Standards Institute
ASTM American Society for Testing Materials

°C Degrees Centigrade
CAS Chemical Abstract Service

Page 3 of 4

# 16. OTHER INFORMATION (Continued)

# **Table of Abbreviations (Continued)**

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

CFR Code of Federal Regulations
CPR Controlled Products Regulations
DOT Department of Transportation
EPA Environmental Protection Agency

°F Degrees Fahrenheit

**FDA** Food & Drug Administration

**Hg** Mercury

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer

**LD** Lethal Dose

mg / kg Milligram per kilogram

mm Millimeter

MSDS Material Safety Data Sheet

**MSHA** Mine Safety and Health Administration

N / A Not Applicable

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

**ppm** Parts per million

**SARA** Superfund Amendment and Reauthorization Act

STEL Short-Term Exposure Limit
TSCA Toxic Substances Control Act
TWA Time - Weighted Average

**U.N.** United Nations

WHMIS Workplace Hazardous Materials Information System

Greater ThanLess Than

Creation Date: 07/00
Revision Date: 06/22/05
Technical Contact: Candi Prado

Senior R&D Specialist Duncan Enterprises 5673 East Shields Avenue

Fresno, CA 93727 559-291-4444 559-291-9444 (Fax)

# Disclaimer

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.